


Æcoustic





PEAA® PANELS ARE CREATIVE SOUND DESIGN

Design something simple...or spectacular! Use PEAA® flat panels adhered to walls and ceilings for clean looks and sound absorption up to .91 NRC, or custom cut PEAA® to create sculptural elements that hide acoustic control in plain sight. Made from up to 70% recycled PET plastic, PEAA® helps reduce landfill waste and can help projects qualify for LEED credit.

PEAA® SPECS:

PANEL SIZE SHEET WEIGHT 9mm x 900mm x 2400mm 12mm x 900mm x 2400mm 24mm x 900mm x 2400mm (12+12mm) NRC (SOUND ABSORBTION RATING): ASTM C423-90A

9mm: 12mm: 24mm: NRC .30 (no air gap) NRC .41 (no air gap) NRC .6

 NRC .30 (no air gap)
 NRC .41 (no air gap)
 NRC .68 (no air gap)

 NRC .50 (20mm air gap)
 NRC .60 (20mm air gap)
 NRC .79 (20mm air gap)

NRC .82 (50mm air gap) NRC .85 (50mm air gap) NRC .91 (50mm air gap)

CERTIFICATIONS

- Fire Rating: ASTM E84 Class A (M1)
- VOC Emissions: ASTM D5116 <.02mg/m2/hour
- Acoustic Absorption: EN ISO 354:2003 12

- Free of Harmful Substances: RoHS 2011/65/EU

- Volatile Organic Compunds: US EPA 5021 A:2003

